

SB-6230/SB-6230R

Component Video CAT5 Extender

COMPONENT CAT5

SB-6230
2Way Component Video Transmitter



Input : 1x Component Video
Output : 2x CAT5

SB-6230R
2Way Component Video Receiver



Input : 1x CAT5 + 1 Loop Output Port
Output : 1x Component Video

FEATURES

01. Support Component Video (YPBPR) CAT5 Transmitter / Receiver / Repeater
02. Provided by the category5 Cable via RJ-45 connector
03. SB-6230 : Input : 1x Component Video
Output : 2x CAT5
04. SB-6230R : Input : 1x CAT5 + 1 Loop Output Port
Output : 1x Component Video
05. Support Full HD resolutions 480i / 480p / 720p / 1080i and 1080p
06. RGB, TINT and BRIGHTNESS adjustment.
07. Extension distance is up to 100M(330FT)
08. Wall mounted Ear Rack included

SPECIFICATIONS

Type of CAT5	CAT5 Transmitter(Tx)/Receiver(Rx)/Repeater(Rxx)
Type of Signals	Component Video (YPBPR) Via 3x RCA connectors
CAT5 connection	Provided by the category5 Cable via RJ-45 connectors CAT5 Repeater for Loop output to Another CAT5 Receiver
Video Bandwidth	225MHz(-3dB), 450MHz(-3dB) Large signal bandwidth
Output Balance Error	-60dB @ 50MHz
High isolation between Amplifier	80dB @ 10MHz
Color proofread	TINT and BRIGHTNESS adjustmen.
HD resolutions	480i / 480p / 720p / 1080i and 1080p
CAT5 Extend distance	100M (330FT) Maximum
Enclosure	wall mount ear includes
Safety Approvals	CE, FCC, VCCI
Dimension (WxDxH)	3.07" x 2.87" x 1.14" (78mm x 73mm x 29mm)
Weight	0.18 kg / 0.39 lb
Power Supply	DC 12V, @0.25A (World Wide Universal AC 100~240V 50/60Hz)

DIAGRAM TYPICAL

