

SB-6345/SB-6345R

Composite Video · Digital · Audio CAT5 Extender

COMPOSITE VIDEO DIGITAL AUDIO CAT5

SB-6345
4Way Composite Video · Digital · Audio Transmitter



Input : 1x Composite Video or Digital Audio and Stereo Audio (AR/AL) + 1 Preview port
Output : 4x CAT5

SB-6345R
2Way Composite Video · Digital · Audio Receiver



Input : 1x CAT5 + 1 Loop Output Port
Output : 2x Composite Video or Digital Audio and Stereo Audio (AR/AL)

FEATURES

- Support Composite Video or Digital Audio (S/PDIF) / Stereo Audio over CAT-5 Transmitter and Repeater + Receiver Extender
- SB-6235 : Input : 1x Composite Video or Digital Audio and Stereo Audio (AR/AL) + 1 Preview port
Output : 4x CAT5
- SB-6235R : Input : 1x CAT5 + 1 Loop Output Port
Output : 2x Composite Video or Digital and Stereo Audio (AR/AL)
- Support HDTV Resolution 480p / 720p / 1080i / 1080p
- Brightness and TINT frequency response adjustment control button on SB-6235R
- Extension distance is up to 100m (330ft)
- Wall mounted Ear Rack included

SPECIFICATIONS

Type of CAT5	Composite Video or Digital Audio(S/PDIF)/Stereo Audio over CAT-5 Transmitter, Repeater and Receiver Extender. Transmitter(TX) / Repeater + Receiver(RX)
Type of Signal	Composite Video or Digital Audio(S/PDIF)/Stereo Audio connectors
Video Bandwidth	225Mhz, -3dB large signal bandwidth 450Mhz, -3dB small signal bandwidth
Output Balance Error	-60dB @ 50Mhz
High Isolation	between Amplifier 80dB @ 10Mhz
Audio- in Impedance	10 Ohms
Audio Frequency Response	20HZ to 20KHz, +/-1db
Safety Approvals	CE, FCC, VCCI
Dimension (WxDxH)	4.44" x 2.87" x 1.14" (113mm x 73mm x 29mm)
Weight	0.2 kg / 0.44 lb
Power Supply	DC 12V, @0.25A (World Wide Universal AC 100~240V 50/60Hz)

DIAGRAM TYPICAL

