

SB-6210/SB-6210R

VGA-Audio CAT5 Extender

VGA AUDIO CAT5

SB-6210
2Way VGA-Audio Transmitter



Input : 1x VGA / Audio
Output : 2x CAT5

SB-6210R
2Way VGA-Audio Receiver



Input : 1x CAT5 + 1 Loop Output Port
Output : 1x VGA / Audio

FEATURES

01. Support VGA-RGBHV & Stereo Audio(AR/AL), CAT5 Transmitter and Repeater + Receiver Extende
02. SB-6210 : Input : 1x VGA+ Audio
Output : 2x CAT5
03. SB-6210R : Input : 1x CAT5 + 1 Loop Output Port
Output : 1x VGA+ Audio
04. Support PC Resolution VGA(640x480) / SVGA(800x600) / XGA(1024x768) / SXGA(1280x1024) / UXGA(1600x1200)
05. Support HDTV Resolution 480p / 720p / 1080i / 1080p
06. Support one Loop Output port
07. Extension distance is up to 100m(330ft)
08. Wall mounted Ear Rack included

SPECIFICATIONS

Type of CAT5	Transmitter (TX) / Repeater + Receiver (RX)
Type of Signal	VGA (RGBHV) & Stereo Audio (AR/AL) connectors
Video Bandwidth	Large Signal Bandwidth : 225Mhz, -3dB Small Signal Bandwidth : 450Mhz, -3dB
Output Balance Error	-60dB @ 50Mhz
High Isolation between Amplifier	80dB @ 10Mh
Audio- in Impedance	10 Ohms
Audio Frequency Response	20HZ to 20KHz, +/-1db
Safety Approvals	CE, FCC, VCCI
Dimension (WxDxH)	3.07" x 2.87" x 1.14" (78mm x 73mm x 29mm)
Weight	0.18 kg / 0.39 lb
Power Supply	DC 12V, @0.25A (World Wide Universal AC 100~240V 50/60Hz)

DIAGRAM TYPICAL

